

Standard-Stocked Product Overview

Product standard-stocked shapes availability

Product Category	Copper alloy UNS no.	Product Description	Solid Bar	Tubes	Rectangles
Extruded and Drawn	C14500	Tellurium Copper	X		
Continuous Cast and Drawn	C51000	Phosphor Bronze 5% A	X		
Continuous Cast and Drawn	C54400	Phosphor Bronze B-2	X		
Extruded and Drawn	AMS 4640-C63000	Nickel-Aluminum Bronze	X		
Extruded and Drawn	AMS 4590-C63020	Nickel-Aluminum Bronze	X	X	
Extruded and Drawn	AMS 4634-C64200	Aluminum Bronze	X		
Extruded and Drawn	C67300	Manganese Bronze	X		
Extruded and Drawn	AMS 4596-C72900	Copper Nickel-Tin Bronze	X		
Extruded and Drawn	AMS 4597-C72900	Copper Nickel-Tin Bronze	X		
Extruded and Drawn	AMS 4598-C72900	Copper Nickel-Tin Bronze		X	
Continuous Cast	C86300	Manganese Bronze	X	X	
Continuous Cast	C89835	Bismuth Tin Bronze	X	X	
Continuous Cast	C90300	Tin Bronze	X		
Continuous Cast	C93200	Leaded Tin Bronze	X	X	X
Continuous Cast	C95400	Aluminum Bronze	X	X	X
Continuous Cast	C95500	Nickel Aluminum Bronze	X		
Continuous Cast	AMS 4880-95510	Nickel Aluminum Bronze		X	
Continuous Cast	C95900	Aluminum Bronze	X		X

Extruded or cast and drawn alloy stocked size schedules

C14500

Standard-stocked product	Extruded and drawn
--------------------------	--------------------

ASTM B301 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
0.375	0.037	0.438	1.125	0.321	3.851	2.000	1.014	12.170
0.500	0.063	0.760	1.250	0.396	4.753	2.250	1.284	15.403
0.625	0.099	1.188	1.375	0.479	5.752	2.500	1.585	19.016
0.750	0.143	1.711	1.500	0.570	6.845	2.750	1.918	23.010
0.875	0.194	2.392	1.625	0.670	8.034			
1.000	0.254	3.042	1.750	0.777	9.318			

C51000

Standard-stocked product	Continuous cast and drawn
--------------------------	---------------------------

ASTM B139 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
3/8	0.035	0.417	13/16	0.167	2.000	1 1/2	0.569	6.833
7/16	0.049	0.583	7/8	0.188	2.250	1 5/8	0.660	7.917
1/2	0.063	0.750	15/16	0.222	2.267	1 3/4	0.771	9.250
9/16	0.083	1.000	1	0.250	3.000	1 7/8	0.882	10.583
5/8	0.097	1.167	1 1/8	0.319	3.833	2	1.007	12.083
11/16	0.118	1.417	1 1/4	0.396	4.750	2 1/4	1.271	15.250
3/4	0.139	1.667	1 3/8	0.472	5.667	2 1/2	1.569	18.833

*H04 hard temper is standard stocked
Hexes available upon request.

Extruded or cast and drawn alloy stocked size schedules

C54400

Standard-stocked product

Continuous cast and drawn

ASTM B139 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
3/8	0.035	0.417	7/8	0.188	2.250	1 3/4	0.771	9.250
7/16	0.049	0.583	15/16	0.222	2.667	1 7/8	0.882	10.583
1/2	0.063	0.750	1	0.250	3.000	2	1.007	12.083
9/16	0.083	1.000	1 1/8	0.319	3.833	2 1/4	1.271	15.250
5/8	0.097	1.167	1 1/4	0.396	4.750	2 1/2	1.569	18.833
11/16	0.118	1.417	1 3/8	0.472	5.667	2 3/4	1.917	23.000
3/4	0.139	1.667	1 1/2	0.569	6.833			
13/16	0.167	2.000	1 5/8	0.660	7.917			

Hexes available upon request.

Extruded or cast and drawn alloy stocked size schedules continued

AMS 4640-C63000

Standard-stocked product

Extruded and drawn

Solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
0.3750	0.030	0.362	1.6250	0.559	6.708	4.2500	3.879	46.542
0.5000	0.054	0.652	1.7500	0.656	7.867	4.5000	4.391	52.689
0.5625	0.068	0.816	1.8750	0.756	9.073	4.7500	4.872	58.468
0.6250	0.082	0.989	2.0000	0.846	10.152	5.0000	5.350	64.196
0.6875	0.102	1.222	2.0625	0.898	10.770	5.2500	5.930	71.158
0.7500	0.119	1.431	2.1250	0.949	11.388	5.5000	6.479	77.739
0.8125	0.141	1.702	2.2500	1.077	12.923	5.7500	7.059	84.700
0.8750	0.165	1.978	2.3750	1.189	14.262	6.0000	7.800	93.600
0.9375	0.189	2.240	2.5000	1.319	15.824	6.5000	9.091	109.091
1.0000	0.213	2.561	2.6250	1.454	17.443	6.7500	9.800	117.600
1.0625	0.240	2.875	2.7500	1.592	19.108	7.0000	10.491	125.895
1.1250	0.267	3.205	2.8750	1.778	21.336	7.5000	12.099	145.186
1.1875	0.297	3.561	3.0000	1.977	23.727	8.0000	13.557	162.679
1.2500	0.334	4.008	3.2500	2.393	28.717	8.5000	15.410	184.920
1.3750	0.399	4.791	3.5000	2.658	31.895	9.0000	17.422	209.075
1.4375	0.444	5.334	3.7500	3.052	36.632	9.5000	19.028	228.336
1.5000	0.480	5.760	4.0000	3.485	41.820	10.0000	21.267	255.200

AMS 4590-C63020

Extruded or cast and drawn alloy stocked size schedules continued

AMS 4634-C64200

Standard-stocked product

Extruded and drawn

Solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
0.1875	0.008	0.092	0.8750	0.170	2.036	2.0000	0.876	10.507
0.2500	0.014	0.170	0.9375	0.194	2.326	2.1250	1.005	12.063
0.3125	0.022	0.268	1.0000	0.222	2.664	2.2500	1.122	13.464
0.3750	0.031	0.369	1.0625	0.249	2.984	2.3750	1.339	16.067
0.4375	0.042	0.509	1.1250	0.279	3.351	2.5000	1.389	16.672
0.5000	0.055	0.665	1.2500	0.343	4.113	2.7500	1.664	19.972
0.5625	0.070	0.838	1.3750	0.415	4.977	3.0000	1.988	23.854
0.6250	0.086	1.026	1.5000	0.504	6.053	4.0000	3.557	42.686
0.6875	0.104	1.252	1.6250	0.582	6.978	5.0000	5.456	65.468
0.7500	0.125	1.504	1.7500	0.674	8.090	6.0000	8.027	96.319
0.8125	0.145	1.736	1.8750	0.771	9.250			

C67300

Standard-stocked product

Extruded and drawn

SAE J463 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
0.3750	0.033	0.397	1.1875	0.334	4.008	1.8750	0.835	10.025
0.5000	0.066	0.787	1.2500	0.358	4.297	2.0000	0.951	11.409
0.5620	0.073	0.870	1.3750	0.452	5.427	2.1250	1.035	12.421
0.7500	0.134	1.603	1.4375	0.487	5.840	2.2500	1.160	13.925
0.8750	0.175	2.105	1.5000	0.535	6.425	2.5000	1.433	17.192
1.0000	0.237	2.848	1.5625	0.578	6.936	2.7500	1.733	20.801
1.0625	0.266	3.190	1.6250	0.605	7.262	3.0000	2.063	24.755
1.1250	0.301	3.611	1.7500	0.731	8.775			

Extruded or cast and drawn alloy stocked size schedules continued

AMS 4596-C72900

Standard-stocked product	Extruded and drawn
--------------------------	--------------------

AMS 4596 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
0.750	0.143	1.714	2.250	1.286	15.427	3.750	3.571	42.853
1.000	0.254	3.047	2.500	1.587	19.046	4.000	4.063	48.758
1.250	0.397	4.761	2.625	1.750	20.998	4.500	5.142	61.709
1.500	0.571	6.857	2.750	1.921	23.046	5.000	6.349	76.184
1.750	0.778	9.333	3.000	2.286	27.426	5.500	7.682	92.182
1.875	0.893	10.713	3.250	2.682	32.188	6.000	9.142	109.705
2.000	1.016	12.189	3.500	3.111	37.330	6.750	11.570	138.845

AMS 4597-C72900

Standard-stocked product	Extruded and drawn
--------------------------	--------------------

AMS 4597 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
0.750	0.143	1.714	1.250	0.397	4.761	1.750	0.778	9.333
1.000	0.254	3.047	1.500	0.571	6.857	2.000	1.016	12.189

AMS 4598-C72900

Standard-stocked product	Extruded and drawn
--------------------------	--------------------

AMS 4598 tubes

Nom size I.D. x O.D.	Weight per inch	Weight per foot	Nom size I.D. x O.D.	Weight per inch	Weight per foot	Nom size I.D. x O.D.	Weight per inch	Weight per foot
2.750 x 4.500	3.458	41.500	3.653 x 6.374	6.896	82.760	6.440 x 8.560	8.210	98.520
3.500 x 5.000	3.374	40.492	3.750 x 5.000	2.765	33.180	7.000 x 8.000	3.7916	45.500
5.500	4.549	54.590	5.000 x 7.000	6.200	74.400			
5.875	5.628	67.540						

*Consult mill for other shapes/sizes.

Continuous-cast alloy stocked size schedules

C86300

Standard-stocked product	Continuous cast
--------------------------	-----------------

ASTM B505 tubes

Nominal size I.D. x O.D.	Weight per inch	Weight per foot	Nominal size I.D. x O.D.	Weight per inch	Weight per foot	Nominal size I.D. x O.D.	Weight per inch	Weight per foot
1 x 1 1/2	0.368	4.417	2 1/2 x 3	0.833	10.000	4 x 4 1/2	1.569	18.833
2	0.764	9.167	3 1/2	1.667	20.000	5	2.639	31.667
2 1/2	1.292	15.500				6	5.326	63.917
3	1.903	22.833	3 x 3 1/2	1.076	12.917			
4	3.556	42.667	4	1.951	23.417	5 x 6	3.528	42.333
			5	4.104	49.250	7	6.396	76.750
1 1/2 x 2	0.514	6.167						
			3 1/2 x 4 1/4	1.875	22.500			
1 3/4 x 2 1/4	0.588	7.055	4 3/4	2.868	34.417			
			5 1/2	4.514	54.167			
2 x 2 1/4	0.368	4.417						
2 1/2	0.667	8.000						
2 3/4	0.972	11.667						
3	1.299	15.583						
3 1/2	2.118	25.417						
4	2.965	35.583						
5	5.111	61.333						
6	7.771	93.250						

ASTM B505 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
1	0.257	3.083	3	2.069	24.833	5	5.806	69.667
1 1/2	0.542	6.500	3 1/2	2.861	34.333	6	8.569	102.833
2	0.944	11.333	4	3.688	44.250			
2 1/2	1.438	17.250	4 1/2	4.792	57.500			

Continuous-cast alloy stocked size schedules continued

C89835

Standard-stocked product	Continuous cast	GreenAlloys™
--------------------------	-----------------	--------------

Tubes

Nominal size I.D. x O.D.	Weight per inch	Weight per foot	Nominal size I.D. x O.D.	Weight per inch	Weight per foot	Nominal size I.D. x O.D.	Weight per inch	Weight per foot
0.500 x 1.250	0.363	4.356	1.750 x 2.250	0.585	7.020	3.250 x 3.750	1.048	12.571
1.500	0.541	6.492	2.500	0.889	10.668	4.000	1.666	20.000
1.750	0.750	9.000	2.750	1.225	14.700	4.500	2.711	32.534
			3.000	1.592	19.104	5.000	3.924	47.088
0.750 x 1.250	0.290	3.480	3.250	2.038	24.457			
1.500	0.470	5.640	3.500	2.486	29.829	3.500 x 4.000	1.238	14.857
1.750	0.677	8.124	3.750	2.952	35.429	4.500	2.296	27.550
2.000	0.921	11.052				5.000	3.509	42.103
2.250	1.194	14.328	2.000 x 2.500	0.658	7.896			
			2.750	0.994	11.928	3.750 x 4.500	1.849	22.187
1.000 x 1.250	0.185	2.220	3.000	1.361	16.332			
1.500	0.362	4.344	3.250	1.810	21.714	4.000 x 5.000	2.583	31.000
1.750	0.572	6.862	3.500	2.248	26.971			
2.000	0.816	9.792	3.750	2.714	32.571	4.250 x 5.000	2.073	24.881
2.250	1.089	13.068	4.000	3.314	39.771			
2.500	1.393	16.716	4.500	4.316	51.788			
2.750	1.729	20.748	5.000	5.523	66.342			
3.000	2.100	25.200						
3.250	2.562	30.743	2.250 x 2.750	0.731	8.772			
3.500	3.000	36.000	3.000	1.100	13.200			
4.000	4.076	48.571	3.250	1.533	18.400			
			3.500	1.981	23.772			
1.250 x 1.500	0.226	2.712	3.750	2.448	29.371			
1.750	0.435	5.220						
2.000	0.680	8.160	2.500 x 3.000	0.804	9.648			
2.250	0.952	11.424	3.250	1.238	14.857			
2.500	1.257	15.084	3.500	1.676	20.114			
2.750	1.592	19.104	3.750	2.152	25.829			
3.000	1.960	23.520	4.000	2.752	33.029			
3.250	2.419	29.029	4.500	3.768	45.221			
3.500	2.857	34.289						
			2.750 x 3.500	1.349	16.114			
1.500 x 1.750	0.267	3.204	3.750	1.819	21.829			
2.000	0.512	6.144	4.000	2.419	29.029			
2.250	0.784	9.408	4.500	3.448	41.370			
2.500	1.089	13.068						
2.750	1.424	17.088	3.000 x 3.500	0.981	11.771			
3.000	1.791	21.492	3.750	1.448	17.371			
3.250	2.248	26.971	4.000	2.057	24.686			
3.500	2.686	32.229	4.500	3.095	37.141			
3.750	3.162	37.943	5.000	4.308	51.695			
4.000	3.743	44.914						
4.500	4.737	56.844						

Solids

Size O.D.	Weight per inch	Weight per foot
1.000	0.276	3.314
1.250	0.429	5.143
1.500	0.610	7.314
1.750	0.829	9.943
2.000	1.076	12.914
2.250	1.352	16.229
2.500	1.667	20.000
2.750	2.010	24.114
3.000	2.390	28.686
3.500	3.156	37.871
4.000	4.160	49.916
4.500	5.247	62.958
5.000	6.459	77.512

Continuous-cast alloy stocked size schedules continued

C90300

Standard-stocked product	Continuous cast	GreenAlloys™
--------------------------	-----------------	--------------

ASTM B505 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
1	0.278	3.333	3	2.361	28.333	5	6.549	78.583
1 1/2	0.597	7.167	3 1/2	3.201	38.417	5 1/2	7.813	93.750
2	1.049	12.583	4	4.215	50.583	6	9.493	113.917
2 1/2	1.646	19.750	4 1/2	5.319	63.833			

Continuous-cast alloy stocked size schedules continued

C93200

Standard-stocked product

Continuous cast

ASTM B505 tubes

Nominal size					Nominal size					Nominal size				
I.D.	x	O.D.	Weight per inch	Weight per foot	I.D.	x	O.D.	Weight per inch	Weight per foot	I.D.	x	O.D.	Weight per inch	Weight per foot
1/2	x	1	0.224	2.692	1 1/8	x	1 3/8	0.206	2.467	1 3/4	x	2	0.327	3.925
		1 1/8	0.291	3.589			1 1/2	0.308	3.701			2 1/8	0.477	5.720
		1 1/4	0.383	4.598			1 5/8	0.411	4.935			2 1/4	0.626	7.514
		1 3/8	0.458	5.495			1 3/4	0.533	6.393			2 3/8	0.776	9.308
		1 1/2	0.561	6.729			2	0.785	9.421			2 1/2	0.935	11.215
		1 3/4	0.766	9.196			2 1/8	0.907	10.879			2 5/8	1.084	13.009
		2	1.019	12.224			2 1/4	1.056	12.673			2 3/4	1.262	15.140
												3	1.645	19.738
5/8	x	1	0.187	2.243	1 1/4	x	1 1/2	0.234	2.804			3 1/4	2.056	24.673
		1 1/8	0.262	3.140			1 5/8	0.336	4.037			3 1/2	2.486	29.832
		1 1/4	0.346	4.150			1 3/4	0.467	5.607			3 3/4	2.879	34.542
		1 3/8	0.439	5.271			1 7/8	0.589	7.065			4	3.533	42.393
		1 1/2	0.533	6.393			2	0.710	8.523			4 1/4	4.019	48.224
							2 1/8	0.841	10.093					
3/4	x	1	0.140	1.682			2 1/4	0.981	11.776	1 7/8	x	2 1/4	0.514	6.168
		1 1/8	0.215	2.579			2 1/2	1.290	15.477			2 3/8	0.673	8.075
		1 1/4	0.308	3.701			2 3/4	1.626	19.514			2 1/2	0.822	9.869
		1 3/8	0.393	4.710			3	2.000	24.000			2 5/8	0.972	11.664
		1 1/2	0.495	5.944			3 1/4	2.411	28.935			2 3/4	1.159	13.907
		1 5/8	0.579	6.953			3 1/2	2.832	33.981			3	1.495	17.944
		1 3/4	0.701	8.411			4	3.869	46.430					
		2	0.944	11.327						2	x	2 1/4	0.355	4.262
		2 1/4	1.215	14.579	1 3/8	x	1 5/8	0.271	3.252			2 3/8	0.551	6.617
		2 1/2	1.523	18.280			1 3/4	0.364	4.374			2 1/2	0.710	8.523
							1 7/8	0.486	5.832			2 5/8	0.869	10.430
7/8	x	1 1/8	0.168	2.019			2	0.636	7.626			2 3/4	1.037	12.449
		1 1/4	0.262	3.140			2 1/8	0.766	9.196			2 7/8	1.215	14.579
		1 3/8	0.336	4.037			2 1/4	0.907	10.879			3	1.430	17.159
		1 1/2	0.449	5.383			2 3/8	1.065	12.785			3 1/4	1.832	21.981
		1 5/8	0.551	6.617			2 1/2	1.206	14.467			3 1/2	2.252	27.028
		1 3/4	0.645	7.738								3 3/4	2.738	24.42
		1 7/8	0.776	9.308	1 1/2	x	1 3/4	0.280	3.364			4	3.308	39.701
		2	0.897	10.766			1 7/8	0.393	4.710			4 1/2	4.364	52.374
		2 1/4	1.168	14.019			2	0.551	6.617			5	5.533	66.393
							2 1/8	0.673	8.075			5 1/2	7.009	84.112
1	x	1 1/4	0.187	2.243			2 1/4	0.822	9.869			6	8.467	101.607
		1 3/8	0.290	3.477			2 3/8	0.981	11.776					
		1 1/2	0.393	4.710			2 1/2	1.131	13.570	2 1/8	x	2 5/8	0.738	8.860
		1 5/8	0.495	5.944			2 3/4	1.458	17.495			2 3/4	0.879	10.542
		1 3/4	0.607	7.290			3	1.841	22.093			2 7/8	1.093	13.121
		1 7/8	0.720	8.636			3 1/4	2.252	27.028			3	1.299	15.589
		2	0.850	10.206			3 1/2	2.664	31.963			3 1/2	2.121	25.458
		2 1/4	1.112	13.346			3 3/4	3.150	37.794					
		2 3/8	1.262	15.140			4	3.710	44.523	2 1/4	x	2 3/4	0.785	9.421
		2 1/2	1.421	17.047			4 1/2	4.776	57.308			2 7/8	0.953	11.439
		2 3/4	1.757	21.084								3	1.150	13.794
		3	2.131	25.570	1 5/8	x	2	0.430	5.159			3 1/8	1.327	15.925
		3 1/4	2.523	30.280			2 1/8	0.579	6.953			3 1/4	1.570	18.841
		3 1/2	2.963	35.551			2 1/4	0.729	8.748			3 1/2	2.000	24.000
		4	4.000	48.000			2 3/8	0.879	10.542			3 3/4	2.467	29.607
							2 1/2	1.028	12.336			4	3.056	36.673
							2 5/8	1.196	14.355			4 1/4	3.533	42.393
							2 3/4	1.355	16.262					
							3	1.748	20.972					

Continuous-cast alloy stocked size schedules continued

C93200

ASTM B505 tubes

Nominal size					Nominal size					Nominal size				
I.D.	x	O.D.	Weight per inch	Weight per foot	I.D.	x	O.D.	Weight per inch	Weight per foot	I.D.	x	O.D.	Weight per inch	Weight per foot
2 3/8	x	2 3/4	0.589	7.065	3 1/2	x	4	1.234	14.804	5 1/4	x	7	6.084	73.009
		2 7/8	0.813	9.757			4 1/4	1.804	21.645					
		3	1.009	12.112			4 1/2	2.346	28.150	5 1/2	x	6	2.103	25.234
		3 1/4	1.355	16.262			4 3/4	2.897	34.766			6 1/2	3.692	44.299
		3 1/2	1.785	21.421			5	3.523	42.280			7	5.421	65.047
		4	2.841	34.093			5 1/4	4.336	52.037			7 1/2	7.262	87.140
							5 1/2	5.065	60.785			8	9.224	110.692
2 1/2	x	2 3/4	0.439	5.271			6	6.495	77.944					
		3	0.869	10.430			6 1/2	8.093	97.121	5 3/4	x	6 3/4	3.832	45.981
		3 1/8	1.065	12.785								7 1/4	5.636	67.626
		3 1/4	1.280	15.364	3 3/4	x	4 1/2	1.916	22.991			7 1/2	6.561	78.729
		3 1/2	1.720	20.636			4 3/4	2.449	29.383			8 1/2	10.654	127.850
		3 3/4	2.187	26.243			5	3.065	36.785					
		4	2.776	33.308			5 1/2	4.636	55.626	6	x	6 1/2	2.252	27.028
		4 1/4	3.318	39.813			6	6.056	72.673			6 3/4	3.121	37.458
		4 1/2	3.804	45.645								7	3.991	47.888
		4 3/4	4.355	52.262	4	x	4 1/2	1.393	16.710			7 1/4	4.907	58.879
		5	5.019	60.224			4 3/4	1.972	23.664			7 1/2	5.832	69.981
		5 1/2	6.467	77.607			5	2.598	31.178			8	7.804	93.645
		6	7.953	95.439			5 1/4	3.430	41.159			8 1/2	9.916	118.991
							5 1/2	4.121	49.458			9	12.112	145.346
2 5/8	x	3 1/2	1.542	18.505			6	5.589	67.065			10	17.103	205.234
							6 1/2	7.178	86.131			11	22.421	269.047
2 3/4	x	3 1/4	0.944	11.327			7	8.907	106.879			12	28.271	339.252
		3 1/2	1.364	16.374			7 1/2	10.748	128.972					
		3 3/4	1.850	22.206			8	12.710	152.523	6 1/2	x	7 1/4	3.374	40.486
		4	2.449	29.383			9	17.000	204.000			7 1/2	4.299	51.589
		4 1/4	3.000	36.000								8	6.262	75.140
		4 1/2	3.495	41.944	4 1/4	x	4 3/4	1.467	17.607			8 1/2	8.374	100.486
		4 3/4	4.056	48.673			5	2.084	25.009			9	10.589	127.065
		5 3/4	6.981	83.776			5 1/4	2.935	35.215			9 1/2	13.093	157.121
							5 1/2	3.617	43.402					
2 7/8	x	4	2.299	27.589			6	5.093	61.121	7	x	7 3/4	3.589	43.065
							6 1/2	6.673	80.075			8	4.598	55.178
3	x	3 1/2	0.963	11.551								8 1/2	6.692	80.299
		3 3/4	1.495	17.944	4 1/2	x	5	1.650	19.800			9	8.916	106.991
		4	2.112	25.346			5 1/4	2.346	28.150			9 1/2	11.421	137.047
		4 1/4	2.664	31.963			5 1/2	3.103	37.234			10	13.897	166.766
		4 1/2	3.140	38.00			6	4.551	54.617			11	19.271	231.252
		4 3/4	3.738	44.860			6 1/2	6.159	73.907			12	25.168	302.019
		5	4.346	52.150			7	7.860	94.318					
		5 1/2	5.869	70.430						7 1/2	x	8 1/2	4.916	58.991
		6	7.280	87.364	4 3/4	x	5 1/4	1.822	21.869			9	7.112	85.346
		6 1/2	8.888	106.654			5 1/2	2.523	30.280			9 1/2	9.617	115.402
		7	10.607	127.290			5 3/4	3.234	38.804			10	12.019	144.224
		8	14.402	172.822			6	3.972	47.664			10 1/2	14.757	177.084
							6 1/2	5.579	66.953					
3 1/4	x	3 3/4	1.037	12.449						8	x	9	5.308	63.701
		4	1.710	20.523	5	x	5 1/2	1.925	23.103			9 1/4	6.505	78.056
		4 1/4	2.271	27.252			5 3/4	2.636	31.626			9 1/2	7.729	92.748
		4 1/2	2.720	32.636			6	3.393	40.710			10	10.196	122.355
		4 3/4	3.318	39.813			6 1/2	5.000	60.000			10 1/2	12.841	154.093
		5	3.925	47.103			7	6.710	80.523			11	15.561	186.729
		5 1/2	5.439	65.271			7 1/2	8.561	102.729			12	21.421	257.047
							8	10.505	126.056			13	28.383	340.598
							9	14.813	177.757					
							10	20.056	240.673					
							11	26.067	312.800					

Continuous-cast alloy stocked size schedules continued

C93200

ASTM B505 tubes

Nominal size I.D. x O.D.	Weight per inch	Weight per foot	Nominal size I.D. x O.D.	Weight per inch	Weight per foot	Nominal size I.D. x O.D.	Weight per inch	Weight per foot
8 1/2 x 9 1/2	5.869	70.430	10 x 11	6.794	81.533	11 1/2 x 13	11.140	133.682
	8.159	97.907		9.533	114.393		13 1/2	14.542
	10.738	128.860		12.551	150.617		14 1/2	21.570
	16.748	200.972		19.159	229.907			
				26.019	312.224	12 x 13 1/2	11.813	141.757
9 x 10	6.159	73.907		42.848	514.171		14	15.131
	8.589	103.065					15	22.477
	8.673	104.075	10 1/2 x 11 1/2	7.065	84.785		16	31.686
	11.327	135.925		9.925	119.103			
	14.224	170.692		13.364	160.374	12 1/2 x 14	12.320	147.840
	17.290	207.477		16.701	200.411			
	31.952	383.429				13 x 14 1/2	12.727	152.726
			11 x 12	7.486	89.832		15	16.858
9 1/2 x 10 1/2	6.477	77.720		10.879	130.542			
	9.075	108.897		13.953	167.439	13 1/2 x 15 1/2	16.907	202.879
	11.850	142.206		20.841	250.093			
	18.355	220.262				14 x 15 1/2	13.430	161.159
							16	17.692
								212.299

ASTM B505 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
3/8	0.043	0.516	2 1/8	1.187	14.243	4 3/4	5.841	70.093
1/2	0.075	0.897	2 1/4	1.327	15.925	5	6.439	77.271
5/8	0.112	1.346	2 3/8	1.477	17.720	5 1/4	7.206	86.467
3/4	0.159	1.907	2 1/2	1.636	19.626	5 1/2	7.916	94.991
7/8	0.215	2.579	2 5/8	1.794	21.533	6	9.336	112.037
1	0.271	3.252	2 3/4	1.972	23.664	6 1/2	10.907	130.879
1 1/8	0.346	4.150	2 7/8	2.150	25.794	7	12.636	151.626
1 1/4	0.421	5.047	3	2.346	28.150	7 1/2	14.486	173.832
1 3/8	0.579	6.953	3 1/4	2.738	32.860	8	16.411	196.935
1 1/2	0.607	7.290	3 1/2	3.168	38.019	9	20.673	248.075
1 5/8	0.701	8.411	3 3/4	3.636	43.626	10	25.607	307.290
1 3/4	0.813	9.757	4	4.178	50.131	11	30.822	369.869
1 7/8	0.925	11.103	4 1/4	4.710	56.523	12	35.701	428.411
2	1.056	12.673	4 1/2	5.271	63.252	13	43.215	518.579

Continuous-cast alloy stocked size schedules continued

C93200

ASTM B505 rectangles

Nominal size					Nominal size					Nominal size				
thickness	x	width	Weight per inch	Weight per foot	thickness	x	width	Weight per inch	Weight per foot	thickness	x	width	Weight per inch	Weight per foot
1/4	x	4	0.466	5.589	3/4	x	1	0.322	3.863	1 1/2	x	2	1.021	12.247
		8	0.986	11.836			2	0.610	7.315			3	1.514	18.164
		12	1.445	17.342			3	0.897	10.767			4	2.123	25.479
							4	1.123	13.479			5	2.575	30.904
3/8	x	4	0.630	7.562			5	1.466	17.589			6	3.158	37.890
		8	1.308	15.669			6	1.726	20.712			7	3.671	44.055
		12	1.932	23.178			7	2.034	24.411			8	4.240	50.877
							8	2.281	27.370			9	4.705	56.466
1/2	x	1	0.226	2.712			9	2.610	31.315			10	5.219	62.630
		2	0.432	5.178			10	2.849	34.192			11	5.740	68.877
		3	0.637	7.644			12	3.377	40.521			12	6.411	76.932
		4	0.788	9.452			14	4.034	48.411					
		5	1.048	12.575			16	4.562	54.740	1 3/4	x	4	2.445	29.342
		6	1.274	15.288			18	4.979	59.753			8	4.918	59.014
		7	1.452	17.425										
		8	1.623	19.479	1	x	1	0.418	5.014	2	x	4	2.781	33.370
		9	1.863	22.356			2	0.712	8.548			8	5.562	66.740
		10	2.048	24.575			3	1.048	12.575			11	7.562	90.740
		12	2.507	30.082			4	1.466	17.589			12	8.322	99.863
		14	2.856	34.274			5	1.884	22.603					
		15	2.993	35.918			6	2.253	27.041	3	x	11	11.096	133.151
							7	2.616	31.397					
5/8	x	1	0.281	3.370			8	2.932	35.178	4	x	4	5.384	64.603
		2	0.521	6.247			9	3.349	40.192			11	14.651	175.808
		3	0.767	9.205			10	3.658	43.890					
		4	0.966	11.589			11	4.089	49.068	6	x	10	19.836	238.027
		5	1.260	15.123			12	4.267	51.205					
		6	1.507	18.082			13	4.822	57.863	6 1/4	x	6 1/4	13.062	156.740
		7	1.753	21.041			14	5.185	62.219					
		8	1.932	23.178			15	5.555	66.658	8	x	8	21.137	253.644
		9	2.247	26.959			16	5.918	71.014					
		10	2.493	29.918			18	6.658	79.890					
		12	2.986	35.836			20	7.185	86.219					
		14	3.479	41.753										
		15	3.603	43.233	1 1/4	x	1	0.507	6.082					
							2	0.959	11.507					
							3	1.411	16.932					
							4	1.788	21.452					
							5	2.315	27.781					
							6	2.767	33.205					
							7	3.219	38.630					
							8	3.596	43.151					
							9	4.123	49.479					
							10	4.575	54.904					
							11	5.027	60.329					
							12	5.390	64.685					
							13	5.925	71.096					
							14	6.377	76.521					
							15	6.671	80.055					

Continuous-cast alloy stocked size schedules continued

C95400

Standard-stocked product	Continuous cast	GreenAlloys™
--------------------------	-----------------	--------------

ASTM B505 tubes

Nominal Size I.D.	x	O.D.	Weight per inch	Weight per foot	Nominal Size I.D.	x	O.D.	Weight per inch	Weight per foot	Nominal Size I.D.	x	O.D.	Weight per inch	Weight per foot
3/4	x	1 1/4	0.278	3.333	2 1/4	x	2 5/8	0.549	6.583	4	x	4 1/2	1.361	16.333
		1 1/2	0.431	5.167			2 3/4	0.694	8.333			4 3/4	1.972	23.667
		1 3/4	0.611	7.333			3	1.007	12.083			5	2.528	30.333
		2	0.819	9.833			3 1/4	1.458	17.500			5 1/2	3.667	44.000
							3 1/2	1.826	21.917			6	5.139	61.667
7/8	x	1 1/4	0.243	2.917			3 3/4	2.243	26.917			7	7.993	95.917
							4	2.674	32.083			8	11.222	134.667
1	x	1 3/8	0.271	3.250										
		1 1/2	0.347	4.167	2 1/2	x	3	0.771	9.250	4 1/4	x	5	2.104	25.250
		1 3/4	0.528	6.333			3 1/4	1.208	14.500					
		2	0.736	8.833			3 1/2	1.590	19.083	4 1/2	x	5	1.708	20.500
		2 1/4	0.972	11.667			3 3/4	1.986	23.833			5 1/4	2.181	26.167
		2 1/2	1.236	14.833			4	2.417	29.000			5 1/2	2.819	33.833
		3	1.840	22.083			4 1/2	3.333	40.000			6	4.301	51.667
		3 1/2	2.618	31.417			5	4.472	53.667			6 1/2	5.639	67.667
		4	3.438	41.250			6	7.076	84.917			7 1/2	8.729	104.750
1 1/4	x	1 3/4	0.417	5.000	2 3/4	x	3 1/4	0.951	11.417	5	x	5 1/2	1.840	22.083
		2	0.625	7.500			3 1/2	1.306	15.667			5 3/4	2.660	31.917
		2 1/4	0.861	10.333			3 3/4	1.729	20.750			6	3.361	40.333
		2 1/2	1.118	13.417			4	2.146	25.750			6 1/2	4.722	56.667
		2 3/4	1.396	16.750			4 1/4	2.590	31.083			7	6.201	74.417
		3	1.729	20.750			4 1/2	3.042	36.500			8	9.431	113.167
		3 1/2	2.514	30.167										
					3	x	3 1/2	1.021	12.250	5 1/2	x	6 1/2	3.639	43.667
1 1/2	x	1 7/8	0.382	4.583			3 3/4	1.431	17.167					
		2	0.486	5.833			4	1.854	22.250	6	x	7	3.9861	47.833
		2 1/4	0.722	8.667			4 1/4	2.299	27.583		x	8	7.236	86.833
		2 1/2	0.986	11.833			4 1/2	2.785	33.417			9	10.868	130.417
		2 3/4	1.278	15.333			5	3.924	47.083					
		3	1.590	19.083			5 1/2	5.090	61.083	6 1/2	x	7 1/2	4.271	51.250
		3 1/2	2.389	28.667			6	6.549	78.583					
		4	3.201	38.417			7	9.396	112.750	7	x	8	4.556	54.667
		4 1/2	4.132	49.583							x	9	8.257	99.083
					3 1/4	x	3 3/4	1.111	13.333		x	10*	12.070	144.840
1 3/4	x	2 1/8	0.438	5.250			4	1.535	18.417					
		2 1/4	0.556	6.667			4 1/2	2.451	29.417	8	x	10*	8.980	107.760
		2 1/2	0.806	9.667			5	3.611	43.333		x	11*	13.490	161.880
		2 3/4	1.111	13.333							x	12*	18.430	221.160
		3	1.431	17.167	3 1/2	x	4	1.208	14.500					
		3 1/4	1.854	22.250			4 1/4	1.653	19.833	8 1/2	x	10 1/2*	9.196	110.352
		3 1/2	2.257	27.08			4 1/2	2.125	25.500					
		3 3/4	2.611	31.333			5	3.264	39.167	9	x	11*	9.980	119.760
		4	2.965	35.583			5 1/2	4.417	53.000	9	x	12*	14.910	178.920
							6	5.882	70.583					
2	x	2 3/8	0.493	5.917						10	x	12*	10.970	131.640
		2 1/2	0.625	7.500	3 3/4	x	4 3/4	2.313	27.750					
		2 3/4	0.910	10.917										
		3	1.243	14.917										
		3 1/4	1.681	20.167										
		3 1/2	2.042	24.500										
		3 3/4	2.438	29.250										
		4	2.861	34.333										
		4 1/2	3.799	45.583										
		5	4.917	59.000										
		6	7.507	90.083										

*Available in 13" minimum lengths and 1" increments above 13".

Continuous-cast alloy stocked size schedules continued

C95400

ASTM B505 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
1/2	0.069	0.833	2 1/4	1.146	13.750	4 3/4	5.083	61.000
5/8	0.097	1.167	2 1/2	1.396	16.750	5	5.625	67.500
3/4	0.139	1.667	2 3/4	1.688	20.250	5 1/2	6.764	81.167
7/8	0.188	2.250	3	2.000	24.000	6	8.194	98.333
1	0.243	2.917	3 1/4	2.389	28.667	6 1/2	9.556	114.667
1 1/4	0.368	4.417	3 1/2	2.771	33.250	7	11.049	132.583
1 1/2	0.521	6.250	3 3/4	3.153	37.833	8	14.333	172.000
1 5/8	0.611	7.333	4	3.576	42.917	9	18.007	216.083
1 3/4	0.701	8.417	4 1/4	4.035	48.417			
2	0.910	10.917	4 1/2	4.500	54.000			

Continuous-cast alloy stocked size schedules continued

C95400

ASTM B505 rectangles

Nominal size					Nominal size					Nominal size				
thickness	x	width	Weight per inch	Weight per foot	thickness	x	width	Weight per inch	Weight per foot	thickness	x	width	Weight per inch	Weight per foot
1/4	x	1	0.103	1.233	3/4	x	3/4	0.192	2.301	1 3/4	x	2	1.027	12.329
		1 1/2	0.144	1.726			1	0.247	2.959			2 1/2	1.274	15.288
		2	0.192	2.301			1 1/2	0.356	4.274			3	1.514	18.164
		2 1/2	0.240	2.877			2	0.466	5.589			4	2.014	24.164
		3	0.281	3.370			2 1/2	0.582	6.986			5	2.507	30.082
		4	0.377	4.521			3	0.692	8.301			10	5.007	60.082
		5	0.459	5.507			3 1/2	0.801	9.616					
		6	0.596	7.151			4	0.918	11.014	2	x	2	1.171	14.055
		12	1.130	13.562			5	1.144	13.726			2 1/2	1.445	17.342
							6	1.404	16.849			3	1.726	20.712
3/8	x	1	0.137	1.644			8	1.836	22.027			3 1/2	2.000	24.000
		1 1/2	0.199	2.384			12	2.678	32.137			4	2.295	27.534
		2	0.260	3.123								6	3.459	41.507
		2 1/2	0.322	3.863	1	x	1	0.315	3.781			12	6.870	82.438
		3	0.384	4.603			1 1/4	0.390	4.685			15	8.918	107.014
		3 1/2	0.452	5.425			1 1/2	0.459	5.507					
		4	0.507	6.082			1 3/4	0.534	6.411	2 1/2	x	2 1/2	1.795	21.534
		5	0.630	7.562			2	0.610	7.315			3	2.137	25.644
		6	0.795	9.534			2 1/2	0.753	9.041			4	2.836	34.027
		8	1.041	12.493			3	0.897	10.767			5	3.527	42.329
		12	1.521	18.247			3 1/2	1.041	12.493			6	4.240	50.877
							4	1.192	14.301			12	8.445	101.342
1/2	x	1/2	0.089	1.068			5	1.479	17.753			15	11.075	132.904
		1	0.171	2.055			6	1.801	21.616					
		1 1/4	0.212	2.548			7	2.068	24.822	3	x	3	2.541	30.493
		1 1/2	0.253	3.041			8	2.370	28.438			4	3.384	40.603
		2	0.329	3.945			12	3.493	41.918			6	5.089	61.068
		2 1/2	0.411	4.932			15	4.925	59.096			15	13.123	157.479
		3	0.486	5.836										
		3 1/2	0.568	6.822	1 1/4	x	1 1/4	0.473	5.671	3 1/2	x	15	15.151	181.808
		4	0.644	7.726			1 1/2	0.568	6.822					
		5	0.801	9.616			1 3/4	0.658	7.890	4	x	4	4.466	53.589
		6	0.993	11.918			2	0.747	8.959			15	17.226	206.712
		8	1.315	15.781			2 1/2	0.925	11.096					
		10	1.630	19.562			3	1.103	13.233	6	x	6	9.986	119.836
		12	1.938	23.260			3 1/2	1.281	15.370					
							4	1.466	17.589					
5/8	x	1	0.205	2.466			5	1.808	21.699					
		1 1/2	0.301	3.616			10	3.637	43.644					
		2	0.397	4.767										
		2 1/2	0.493	5.918	1 1/2	x	1 1/2	0.671	8.055					
		3	0.589	7.068			1 3/4	0.774	9.288					
		4	0.781	9.370			2	0.890	10.685					
		5	0.973	11.671			2 1/2	1.103	13.233					
		6	1.199	14.384			3	1.308	15.699					
		8	1.562	18.740			3 1/2	1.527	18.329					
							4	1.740	20.877					
							5	2.144	25.726					
							6	2.651	31.808					
							12	5.130	61.562					
							15	6.911	82.932					

Continuous-cast alloy stocked size schedules continued

C95500

Standard-stocked product*	Continuous cast	GreenAlloys™
---------------------------	-----------------	--------------

ASTM B505 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
1.000	0.243	2.917	2.500	1.424	17.083	4.000	3.646	43.750
1.500	0.535	6.417	3.000	2.035	24.417			
2.000	0.924	11.083	3.500	2.806	33.667			

AMS 4880-C95510

Standard-stocked product	Continuous cast
--------------------------	-----------------

Tubes

Nom. Size O.D. x I.D.	Weight Per Inch	Weight Per Foot	Nom. Size O.D. x I.D.	Weight Per Inch	Weight Per Foot	Nom. Size O.D. x I.D.	Weight Per Inch	Weight Per Foot
2.000 x 1.000	0.739	8.868	3.500 x 1.500	2.476	29.712	5.750 x 4.250	3.979	47.748
2.250 x 1.250	0.867	10.404	2.500	1.639	19.668	6.000 x 3.000	6.469	77.628
1.500	0.707	8.484	3.750 x 2.000	2.437	29.244	3.750	5.556	66.672
2.500 x 1.000	1.242	14.904	2.500	1.943	23.316	4.500	4.433	53.196
1.500	1.002	12.024	2.750	1.764	21.168	5.375	2.397	28.764
1.750	0.821	9.852	4.000 x 2.000	2.860	34.320	6.500 x 4.000	6.608	79.296
2.750 x 1.500	1.254	15.048	2.500	2.505	30.060	5.000	4.704	56.448
1.750	1.008	12.096	4.125 x 3.125	1.923	23.076	7.000 x 4.000	8.000	96.000
2.875 x 1.875	1.149	13.788	4.250 x 3.000	2.311	27.732	8.000 x 6.000	7.347	88.164
3.000 x 1.500	1.515	18.180	4.500 x 2.500	3.327	39.924	8.500 x 6.000	8.866	106.392
2.000	1.210	14.520	3.000	2.792	33.504	6.500	7.568	90.816
3.125 x 2.125	1.378	16.536	5.000 x 3.000	4.207	50.484	11.000 x 9.000	9.867	118.404
3.250 x 2.000	1.657	19.884	3.750	3.012	36.144	12.000 x 10.250	9.794	117.528
2.250	1.512	18.144	5.500 x 3.500	4.396	52.752	13.000 x 10.000	16.564	198.768

Continuous-cast alloy stocked size schedules continued

C95900

Standard-stocked product

Continuous cast

GreenAlloys™

ASTM B505 rectangles

Nominal size thickness x width	Weight per inch	Weight per foot	Nominal size thickness x width	Weight per inch	Weight per foot	Nominal size thickness x width	Weight per inch	Weight per foot
1/4 x 1	0.160	1.917	1/2 x 1	0.236	2.833	1 x 1	0.396	4.750
2	0.285	3.417	2	0.431	5.167	2	0.715	8.583
3	0.313	3.750	3	0.521	6.250	2 1/2	0.785	9.417
4	0.542	6.500	4	0.813	9.750	3	0.931	11.167
5	0.667	8.000	5	1.007	12.083	4	1.229	14.750
6	0.799	9.583	6	1.194	14.333	5	1.514	18.167
7	0.924	11.083	7	1.389	16.667	6	1.813	21.750
8	1.049	12.583	8	1.576	18.917	7	2.313	27.750
9	1.181	14.167	9	1.771	21.250	8	2.632	31.583
10	1.306	15.667	10	1.958	23.500	9	2.951	35.417
12	1.563	18.750	12	2.319	27.833	10	3.264	39.167
						12	3.951	47.417
3/8 x 1	0.201	2.417	5/8 x 1 1/2	0.326	3.917	1 1/2 x 4	1.792	21.500
2	0.361	4.333						
3	0.424	5.083	3/4 x 1	0.319	3.833	1 3/4 x 2 1/2	1.257	15.083
4	0.681	8.167	2	0.576	6.917			
5	0.833	10.000	3	0.729	8.750	2 x 5	2.771	33.250
6	0.993	11.917	4	1.083	13.000			
7	1.153	13.833	5	1.340	16.083	2 1/2 x 4	2.868	34.417
8	1.313	15.750	6	1.597	19.167	7	4.757	57.083
9	1.472	17.667	7	1.847	22.167			
10	1.632	19.583	8	2.104	25.250			
12	1.958	23.500	9	2.361	28.333			
			10	2.611	31.333			
			12	3.118	37.417			

ASTM B505 rectangles (metric sizes)

Nominal size thickness x width	Weight per inch	Weight per foot	Nominal size thickness x width	Weight per inch	Weight per foot	Nominal size thickness x width	Weight per inch	Weight per foot
20 mm x 50 mm	0.486	5.833	20 mm x 100 mm	0.944	11.333	20 mm x 160 mm	1.507	18.083
20 mm x 75 mm	0.711	8.532	20 mm x 125 mm	1.174	14.083			
20 mm x 80 mm	0.764	9.167	20 mm x 150 mm	1.390	16.680			

ASTM B505 solids

Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot	Size O.D.	Weight per inch	Weight per foot
1	0.236	2.833	2	0.875	10.500	3 1/2	2.694	32.333
1 1/4	0.354	4.250	2 1/4	1.104	13.250	4	3.431	41.167
1 1/2	0.507	6.083	2 1/2	1.347	16.167	4 1/2	4.549	54.583
1 3/4	0.701	8.417	3	1.938	23.250	5	5.368	64.417